

EN 200 / EN 220

5,6" TFT LCD monitor without / with service kit



Specifications

Screen size: 87 x 116 mm, 5,6"

Effective display area: 83,52 x 111,36 mm

Dot matrix: 320 x 240

Pixel distance: 0,116 x 0,348

Brightness: 270 cd / m²

Video input: 1 Vp-p FBAS

Audio input: 50 mV (min.), stereo

Audio output: built-in 4cm, 200 mW speaker, stereo earphone

Control: brightness, contrast, colour, volume

Power source: 9 ~ 20 V DC

Power consumption: 8 W max. at 12 V DC

Operating temperature: 0°C ~ +50°C

Colour casing: black

Dimensions: 162 (W) x 131 (H) x 54 (D) mm

Weight: 482 g (w/o service kit), 2,95 kg (with service kit)

Service kit:

bag, accumulator, charger, mains supply, cables

Important Note!!

For EN220, Fully Charge Battery with charger before use it.

Battery care information

- Completely use the battery till it is drained and then fully recharge the battery again. This is highly recommended for extending battery life.
- Keep the battery and the contact terminals clean.
- Avoid exposing the battery to extreme heat and cold.
- Use the battery. If possible, avoid letting your battery sit dormant for long periods of time.
- Charge and re-condition a battery after an extended idle period.